

Material SAFETY DATA SHEET Strongcoat Topping T - Base

1: PRODUCT AND COMPANY IDENTIFICATION

| Product Name: | Strongcoat Topping T - Base | | |
|----------------|---|---------------------|--|
| Description: | Base component of two parts trowel applied epoxy flooring | | |
| Manufacturer: | Ayla Lebanon | | |
| | Port, Jamarek Street (Face Port Pharmacy) | , Rbeiz Bldg | |
| | Beirut, Lebanon | | |
| | Tel.: +961 1 444 562 | Fax: +961 1 444 563 | |
| | www.dcp-int.com | | |
| Date Prepared: | 04.06.2008 | | |
| MSDS Number: | DCP/05/04/20-B | | |

2: COMPOSITION / INFORMATION ON INGREDIENTS

| Composition: | Epoxy resin, inert fillers. | | | |
|--|-----------------------------|-------------------|------------|----|
| Hazardous Ingredient(s) | Symbol | Risk Phrases | CAS No. | % |
| Epoxy resin (Number average molecular weight < 700) | Xi, N | R36/38, 43, 51/53 | 25068-38-6 | 80 |

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

| Hazard Information: | Irritating to eyes and skin. May cause sensitization by skin contact. | |
|---------------------|--|--|
| | Toxic to aquatic organism, may cause long-term affects in the aquatic environment. | |
| Classification: | Xi, N. R36/38, 43, 51/53 | |



4: FIRST AID MEASURES

| Eyes: | Irrigate immediately with copious quantities of water for 15 minutes. Obtain medical attention urgently. |
|-------------|--|
| Skin: | Wash immediately with soap and water or suitable skin cleanser. Remove |
| | contaminated clothes and shoes. Obtain medical advice if skin disorders develop. |
| Inhalation: | Remove from exposure, obtain medical attention if respiratory irritation develops or if breathing becomes difficult. |
| Ingestion: | Rinse mouth thoroughly. Drink plenty of water. Do not induce vomiting. Obtain medical attention. Beware of aspiration if vomiting occurs. |

5: FIRE FIGHTING MEASURES

| Flash Point (Closed Cup): | > 200°C. |
|--------------------------------|--|
| Extinguishing Media: | Carbon dioxide, powder, foam or water. |
| Personal Protective Equipment: | Self-contained breathing apparatus. |
| Special Exposure Hazards: | Toxic fumes. Carbon oxides. |

6: ACCIDENTAL RELEASE MEASURES

| Personal Precautions: | Wear suitable protective clothing, gloves and eye/face protection. |
|-----------------------------|---|
| Environmental Precautions: | Prevent entry into drains, sewers and water courses. |
| Decontamination Procedures: | Soak up with inert absorbent such as sand. Gather into labeled containers. Dispose off as applicable regulations. |

| _ | | | | | | |
|----|----|------|------|-----|------|-------|
| 7: | | | | | STOR | V C E |
| 1. | ПA | INDL | ING. | AND | JUK | AGE |

| Handling: | Maintain good standards of personal hygiene. Avoid skin and eye contact. Do not eat, drink or smoke whilst using this product. Ensure adequate ventilation. |
|-----------|--|
| Storage: | Keep container tightly closed in a cool dry area. |

Storage:

Keep container tightly closed in a cool dry area.

8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

| Eye Protection: | Safety glasses/goggles. |
|-------------------------|---|
| Skin Protection: | Impervious gloves (e.g. PVC). Suitable protective clothing. |
| Respiratory Protection: | Organic chemical cartridge respirator, if needed. |
| Hygiene Measures: | Change contaminated clothing and clean before re-use. |
| Engineering Controls: | No specific ventilation requirements noted. |
| Exposure Guidelines: | None assigned. |
| | |

| Issue No.: | 01 | Rev. No.: | 00 | Strongcoat Topping T – Base | Page 2 of 5 |
|------------|----|-----------|----|-----------------------------|-------------|
| | | | | | |



9: PHYSICAL AND CHEMICAL PROPERTIES

| Form: | Liquid |
|--------------------------------|----------------|
| Colour: | Straw colour |
| Odour: | Mild |
| pH (concentrate): | Not applicable |
| Boiling Point (°C): | > 200 |
| Flash Point (closed cup) (°C): | > 200 |
| Autoflammability (°C): | Not determined |
| Explosive Properties (%): | Not Known |
| Vapor Pressure (KPa @20°C): | 0.001 |
| Relative Density (@25°C): | 1.185 |
| Water Solubility: | Insoluble |

10: STABILITY AND REACTIVITY

| Stability: | Stable: reacts with compounds containing amino, hydroxyl or carboxyl groups to give stable, cross linked materials. |
|-----------------------------------|---|
| Conditions to Avoid: | None Known. |
| Chemical Incompatibility: | Strong acids. Strong alkalis. Strong oxidizing agents. |
| Hazardous Decomposition Products: | Thermal decomposition yield oxides of carbon, toxic fumes. |

11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Acute Oral effect LD50 > 5000 mg/kg. Classified as moderate sensitizer.

Health Effects

| On Eyes: | Slight irritation (rabbit). |
|----------------|---|
| On Skin: | Moderate irritation (rabbit). |
| By Inhalation: | May cause respiratory irritation. |
| By Ingestion: | May cause irritation of mouth, throat and digestive tract. |
| Chronic: | Repeated and prolonged skin contact may lead to skin disorders. |

00



12: ECOLOGICAL INFORMATION

| Environmental Assessment: | When used and disposed as intended, no adverse environmental effects are foreseen. |
|---------------------------|--|
| Mobility: | Mobile liquid. Insoluble in water. |
| Degradability: | Not readily biodegradable. |
| Bioaccumulation: | Not expected to be bioaccumulate. |
| Acute Fish Toxicity: | Ecotoxic to fish/daphnia/algae. |

13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

| Unused Product: | Dispose off through an authorized waste contractor to a licensed site. | |
|-----------------------------|--|--|
| Used/ Contaminated Product: | As for unused product. | |
| Packaging: | Must be disposed off through an authorized waste contractor. | |

14: TRANSPORT INFORMATION



UN Number:

3082

Transport Name:

Environmentally hazardous substance, liquid n.o.s (Epoxy resin).

| Transport Type: | | Class: | Pack Group: | Marine Pollutant |
|-----------------|-----------|--------|-------------|------------------|
| At Sea | IMO | 9 | Ш | No |
| Air Transport | IATA/ICAO | 9 | Ш | |
| At land | RID/ADR | 9 | 111 | |



15: REGULATORY INFORMATION

| Hazard Label Data: | Xi | N Dangerous for the environment | |
|-----------------------|---|---|--|
| Named Ingredients: | Epoxy resin (Number average molecular weight < 700) | | |
| UN Number: | 3082 | | |
| Risk Phrases: | | | |
| | R36/38 | Irritating to eyes and skin. | |
| | R43 | May cause sensitization by skin contact. | |
| | R51/53 | Toxic to aquatic organisms, may cause long-term adverse in the aquatic environment. | |
| Safety Phrases: | | | |
| | S24/25 | Avoid contact with skin and eyes. | |
| | S26 | In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. | |
| | S37/39 | Wear suitable gloves and eye/face protection. | |
| 16: OTHER INFORMATION | | | |

04/06/2008

Issue Date:

Disclaimer:

Revised Date:

The information contained herein is derived from the best available sources and is believed to be accurate. However, no guarantee is expressed or implied regarding the accuracy of the data given in the use of this product.

| 1 | ssue No.: | 01 | Rev. No.: | 00 | Strongcoat Topping T – Base | Page | 5 of 5 |
|---|-----------|----|-----------|----|-----------------------------|------|--------|
| | | | | | | | |