

# Material SAFETY DATA SHEET Strongcoat UN101 - Hardener

### 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Strongcoat UN101 - Hardener

Description: Hardener component of two part High build, Solvent free, epoxy floor

coating

Manufacturer: Ayla for Building Materials Industry & Trade

Al-Karadeh, Arsat Al-Hindia, Baghdad

Tel.: +964 790 1488 730

www.dcp-int.com

Date Prepared: 19.01.17

MSDS Number: DCP/05/04/96-H

### 2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition: Epoxy resin hardening agent.

Hazardous Ingredient(s) Symbol Risk Phrases CAS No. %

3-aminomethyl-3,5,5-tri

-methylcyclohexylamine C, Xn R21/22, 34, 43, 52/53 2855-13-2 30 - 70 Benzyl alcohol Xn R20/22 100-51-6 20 - 45

Refer to Section 8 for Occupational Exposure Limits.

#### 3: HAZARDS IDENTIFICATION

Hazard Information: Corrosive.

Harmful by inhalation, in contact with skin and if swallowed.

Causes burns.

Irritating to eyes and skin.

May cause sensitisation by skin contact.

Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Classification: C, Xn. R20/21/22, 34, 43, 52/53.



#### 4: FIRST AID MEASURES

Eyes: Irrigate opened eye immediately with copious quantities of water for 15

minutes. Obtain medical attention immediately.

Skin: Wash immediately with soap and water or suitable skin cleanser. Remove

contaminated clothes and shoes. Obtain medical advice if irritation

persists.

Inhalation: Remove from exposure; obtain medical attention if respiratory irritation

develops or if breathing becomes difficult.

Ingestion: Drink plenty of water. Do not induce vomiting. Obtain medical attention.

Beware of aspiration if vomiting occurs.

#### 5: FIRE FIGHTING MEASURES

Flash Point (Closed Cup): > 100°C.

Extinguishing Media: CO<sub>2</sub>, extinguishing powder or water jet. Fight larger fires with water jet or

alcohol-resistant foam. For safety reasons do not use Water with a full

water jet.

Personal Protective Equipment: Self-contained breathing apparatus. Standard aluminized suit.

Special Exposure Hazards: Toxic fumes. Carbon monoxide (CO), Nitrogen oxides (NOx).

# **6: ACCIDENTAL RELEASE MEASURES**

Personal Precautions: Ensure adequate ventilation immediately issue NO SMOKING and NO

NAKED FLAMES warnings. Wear suitable protective clothing, gloves and

eye/face protection.

Environmental Precautions: Prevent entry into drains, sewers and water courses.

Decontamination Procedures: Soak up with inert absorbent like sand. Gather into labeled containers.

Dispose off as applicable regulations.

#### 7: HANDLING AND STORAGE

Handling: Maintain good standards of personal hygiene. Avoid skin and eye contact.

Do not eat, drink or smoke whilst using this product. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory

equipment.

Storage: Keep container tightly closed in a cool dry area away from sources of heat

and out of direct sunlight to avoid pressure build up. Store in conformity with local fire regulations. Store away from sources of ignition. Keep away

from food containers. Store at 15 - 25°C.



#### 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Eye Protection: Tightly sealed safety glasses/goggles.

Skin Protection: Impervious gloves (e.g. PVC). Suitable protective clothing.

Respiratory Protection: Breathing filters apparatus.

Hygiene Measures: Change contaminated clothing and clean before re-use.

Engineering Controls: Use only in well ventilated area. Local exhaust ventilation is

recommended.

Exposure Guidelines: None assigned.

### 9: PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid

Colour: Yellowish

Odour: Amine-like Boiling Point (°C): > 200

Flash Point (closed cup) (°C): > 100

Autoflammability (°C): Product is not self igniting

Relative Density (@25°C): 1.0 - 1.1

Water Solubility: Not miscible or difficult to mix

### 10: STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to Avoid: Humidity.

Chemical Incompatibility: Strong acids. Strong alkalis. Strong oxidizing agents.

Hazardous Decomposition Products: Thermal decomposition yield oxides of Carbon, nitrogen compounds.

#### 11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Expected oral LD50, rat > 1000 mg/kg.

Classified as skin sensitizer.

#### **Health Effects**

On Eyes: Strong caustic effect.

On Skin: Corrosive - causes burns. May cause sensitization.

By Inhalation: Harmful by inhalation. May cause respiratory irritation.

By Ingestion: Harmful if swallowed. May cause irritation of mouth, throat and digestive

tract. Ingestion of significant amounts may result in severe systemic

effects.

Issue No.:	01	Rev. No.:	00	Strongcoat UN101 – Hardener	Page	3 c	of 5	
------------	----	-----------	----	-----------------------------	------	-----	------	--



### 12: ECOLOGICAL INFORMATION

Environmental Assessment: When used and disposed as intended, no adverse environmental effects

are foreseen.

Mobile liquid. Insoluble in water.

Degradability: Not readily biodegradable.

Bioaccumulation: Not Known.

Acute Fish Toxicity: Expected to be ecotoxic to fish/daphnia/algae.

## 13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product: Classified as a special waste. May be reacted with base component to give

an inert polymeric material.

Used/ Contaminated Product: Classified as a special waste. Dispose off through an authorized waste

contractor to a licensed site.

Packaging: Must be disposed off through an authorized waste contractor.

# 14: TRANSPORT INFORMATION



UN Number: 2289

Transport Name: Corrosive substances.

Transport Type:		Class:	Pack Group:	Marine Pollutant
At Sea	IMDG	8	III	No
Air Transport	IATA/ICAO	8	III	
At land	RID/ADR	8	III	



#### 15: REGULATORY INFORMATION

Hazard Label Data:

Corrosive

Named Ingredients: 3-aminomethyl-3,5,5-trimethylcyclohexylamine.

Risk Phrases: R20/21/22 Harmful by inhalation, in contact with skin and if

swallowed.

R34 Causes burns.

R43 May cause sensitisation by skin contact.

R52/53 Harmful to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Safety Phrases:

S26 In case of contact with eyes, rinse immediately with

plenty of water and seek medical advice.

S28 After contact with skin, wash immediately with plenty of

water.

S36/37/39 Wear suitable protective clothing, gloves and eye/face

protection.

S45 In case of accident or if you feel unwell, seek medical

advice immediately (show the label where possible).

S60 This material and its container must be disposed of as

hazardous waste.

# **16: OTHER INFORMATION**

Issue Date: 19/01/2017 Revised Date:

Disclaimer: The information contained herein is derived from the best available sources and is

believed to be accurate. However, no guarantee is expressed or implied regarding

the accuracy of the data given in the use of this product.