



## SAFETY DATA SHEET STRONGCOAT WD RESIN CLEAR

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** STRONGCOAT WD RESIN CLEAR  
**Internal identification** SCWDR/6

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Component of epoxy coating system  
**Uses advised against** None

#### 1.3. Details of the supplier of the safety data sheet

**Supplier** Don Construction Products Ltd.  
 Churnetside Business Park  
 Station Road  
 Cheddleton  
 Staffordshire ST13 7RS  
  
 Tel: 01538 361799  
 Fax: 01538 361899  
 E-Mail: info@donconstruction.co.uk

#### 1.4. Emergency telephone number

**Emergency telephone** 01538 361799 Mon-Fri 8.30am - 5.00pm (excluding Bank Holidays)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification

**Physical hazards** Not Classified


**Classification (67/548/EEC or 1999/45/EC)** Xi;R36/38. R43. N;R51/53.

**Human health** The liquid is irritating to eyes and skin. Risk of sensitisation by skin contact

**Environmental** The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

#### 2.2. Label elements

##### Pictogram



**Signal word** Warning

## STRONGCOAT WD RESIN CLEAR

<b>Hazard statements</b>	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.
<b>Precautionary statements</b>	P262 Do not get in eyes, on skin, or on clothing. P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P313 Get medical advice/attention.
<b>Contains</b>	BPF EPOXY RESIN, C13/15 ALKYLGLYCIDYL ETHER, EPOXY RESIN (Number average MW <= 700 )
<b>Supplementary precautionary statements</b>	P501 Dispose of contents/container in accordance with local regulations.

### 2.3. Other hazards

#### SECTION 3: Composition/information on ingredients

##### 3.2. Mixtures

<b>BPF EPOXY RESIN</b>		<b>30-60%</b>
CAS number: 55492-52-9		
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Skin Irrit. 2 - H315	Xi;R36/38. R43.	
Eye Irrit. 2 - H319		
Skin Sens. 1 - H317		
<b>EPOXY RESIN (Number average MW &lt;= 700 )</b>		<b>10-30%</b>
CAS number: 25068-38-6	EC number: 500-033-5	REACH registration number: 01-2119456619-26
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Skin Irrit. 2 - H315	R43 Xi;R36/38 N;R51/53	
Eye Irrit. 2 - H319		
Skin Sens. 1 - H317		
Aquatic Chronic 2 - H411		
<b>C13/15 ALKYLGLYCIDYL ETHER</b>		<b>10-30%</b>
CAS number: 68081-84-5	EC number: 268-358-2	
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Skin Irrit. 2 - H315	Xi;R36/38. N;R51/53. R43.	
Eye Irrit. 2 - H319		
Skin Sens. 1 - H317		
Aquatic Chronic 2 - H411		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**Composition comments** Epoxy resin blend.

## STRONGCOAT WD RESIN CLEAR

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Remove affected person from source of contamination.
<b>Inhalation</b>	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. Get medical attention immediately.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.
<b>Eye contact</b>	Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	This is unlikely to occur but symptoms similar to those of ingestion may develop.
<b>Ingestion</b>	May cause discomfort if swallowed.
<b>Skin contact</b>	Skin irritation. May cause an allergic skin reaction.
<b>Eye contact</b>	Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

#### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	Treat symptomatically.
-----------------------------	------------------------

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Extinguish with foam, carbon dioxide or dry powder.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards</b>	Toxic gases/vapours/fumes of: Oxides of the following substances: Carbon. Nitrogen.
<b>Hazardous combustion products</b>	Oxides of carbon. Oxides of nitrogen.

#### 5.3. Advice for firefighters

<b>Protective actions during firefighting</b>	No specific firefighting precautions known.
<b>Special protective equipment for firefighters</b>	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Provide adequate ventilation. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Avoid contact with skin and eyes.
-----------------------------	--

#### 6.2. Environmental precautions

## STRONGCOAT WD RESIN CLEAR

**Environmental precautions** Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillages with sand, earth or any suitable absorbent material.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Absorb spillage with sand or other inert absorbent. Collect spillage in containers, seal securely and deliver for disposal as hazardous waste.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Provide adequate ventilation. Good personal hygiene procedures should be implemented. Do not eat, drink or smoke when using the product.

**Advice on general occupational hygiene** Promptly remove any clothing that becomes contaminated. Wash contaminated clothing before reuse. Wash after use and before eating, smoking and using the toilet.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep separate from food, feedstuffs, fertilisers and other sensitive material. Store in closed original container at temperatures between 5°C and 30°C. Store in a cool and well-ventilated place.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

### 8.2. Exposure controls

#### Protective equipment



**Appropriate engineering controls**

Provide adequate general and local exhaust ventilation.

**Personal protection**

Always check applicability with your supplier of protective equipment.

**Eye/face protection**

If there is a risk of splashing, wear chemical resistant goggles or visor approved to BS EN166.

**Hand protection**

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Nitrile gloves to BSEN374 are recommended. Break through times can vary depending on thickness, use and source. Change gloves regularly.

**Other skin and body protection**

Wear suitable protective clothing as protection against splashing or contamination. Wear apron or protective clothing in case of contact.

**Hygiene measures**

Provide eyewash station. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin becomes contaminated. Wash contaminated clothing before reuse.

**Respiratory protection**

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

## STRONGCOAT WD RESIN CLEAR

<b>Thermal hazards</b>	None
<b>Environmental exposure controls</b>	Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Clear liquid.
<b>Colour</b>	Amber.
<b>Odour</b>	Slight. Aromatic.
<b>Odour threshold</b>	Not determined.
<b>pH</b>	Not applicable.
<b>Melting point</b>	Not applicable.
<b>Initial boiling point and range</b>	Not determined.
<b>Flash point</b>	Not determined.
<b>Evaporation rate</b>	Not determined.
<b>Evaporation factor</b>	Not determined.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	Not applicable.
<b>Other flammability</b>	Not applicable.
<b>Vapour pressure</b>	Not determined.
<b>Vapour density</b>	Not determined.
<b>Relative density</b>	1.38 @ 20°C
<b>Bulk density</b>	Not determined.
<b>Solubility(ies)</b>	Insoluble in water.
<b>Partition coefficient</b>	Not determined.
<b>Auto-ignition temperature</b>	Not applicable.
<b>Decomposition Temperature</b>	Not applicable.
<b>Viscosity</b>	1350 cP @ 20°C
<b>Explosive properties</b>	Not applicable.
<b>Explosive under the influence of a flame</b>	Not considered to be explosive.
<b>Oxidising properties</b>	Not determined.
<b>Comments</b>	Information given is applicable to the product in its ready-to-use form.

#### 9.2. Other information

<b>Other information</b>	None.
<b>Refractive index</b>	Not determined.
<b>Particle size</b>	Not applicable.

## STRONGCOAT WD RESIN CLEAR

<b>Molecular weight</b>	Not determined.
<b>Volatility</b>	Not determined.
<b>Saturation concentration</b>	Not determined.
<b>Critical temperature</b>	Not determined.
<b>Volatile organic compound</b>	Not determined.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

<b>Reactivity</b>	The following materials may react with the product: Acids. Strong alkalis. Strong oxidising agents.
-------------------	---

#### 10.2. Chemical stability

<b>Stability</b>	Stable at normal ambient temperatures.
------------------	--

#### 10.3. Possibility of hazardous reactions

<b>Possibility of hazardous reactions</b>	Under normal conditions of storage and use, hazardous reactions will not occur. Considerable exothermic reaction can occur when mixed with epoxide hardeners.
---	---

#### 10.4. Conditions to avoid

<b>Conditions to avoid</b>	Avoid contact with acids and oxidising substances.
----------------------------	--

#### 10.5. Incompatible materials

<b>Materials to avoid</b>	Strong acids. Strong alkalis. Strong oxidising agents.
---------------------------	--

#### 10.6. Hazardous decomposition products

<b>Hazardous decomposition products</b>	Oxides of carbon. Oxides of nitrogen.
---	---------------------------------------

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

<b>Toxicological effects</b>	No information available.
------------------------------	---------------------------

#### Acute toxicity - oral

<b>Notes (oral LD<sub>50</sub>)</b>	No specific test data are available.
-------------------------------------	--------------------------------------

#### Acute toxicity - dermal

<b>Notes (dermal LD<sub>50</sub>)</b>	No specific test data are available.
---------------------------------------	--------------------------------------

#### Acute toxicity - inhalation

<b>Notes (inhalation LC<sub>50</sub>)</b>	No specific test data are available.
---	--------------------------------------

#### Skin corrosion/irritation

<b>Skin corrosion/irritation</b>	Irritating to skin.,Prolonged or repeated contact with skin may cause irritation, redness and dermatitis.
----------------------------------	---

<b>Animal data</b>	No specific test data are available.
--------------------	--------------------------------------

<b>Human skin model test</b>	No specific test data are available.
------------------------------	--------------------------------------

<b>Extreme pH</b>	No specific test data are available.
-------------------	--------------------------------------

#### Serious eye damage/irritation

<b>Serious eye damage/irritation</b>	Irritation of eyes is assumed.
--------------------------------------	--------------------------------

## STRONGCOAT WD RESIN CLEAR

### Respiratory sensitisation

**Respiratory sensitisation** No specific test data are available.

### Skin sensitisation

**Skin sensitisation** Sensitising.

### Germ cell mutagenicity

**Genotoxicity - in vitro** No specific test data are available.

**Genotoxicity - in vivo** No specific test data are available.

### Carcinogenicity

**Carcinogenicity** No specific test data are available.

**Target organ for carcinogenicity** No specific target organs known.

**IARC carcinogenicity** Not listed.

### Reproductive toxicity

**Reproductive toxicity - fertility** No specific test data are available.

### Specific target organ toxicity - single exposure

**STOT - single exposure** No specific test data are available.

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** No specific test data are available.

### Aspiration hazard

**Aspiration hazard** Not relevant.

**General information** No specific health hazards known.

**Inhalation** May cause some discomfort in poorly ventilated areas.

**Ingestion** May cause discomfort if swallowed.

**Skin contact** Prolonged or repeated exposure may cause severe irritation. May cause sensitisation by skin contact.

**Eye contact** Irritating to eyes.

**Acute and chronic health hazards** Irritating to skin. Irritating to eyes. May cause sensitisation by skin contact.

**Route of entry** Skin and/or eye contact

**Target organs** Eyes Skin

**Medical symptoms** Skin irritation. Irritation of eyes and mucous membranes.

**Medical considerations** Pre-existing eye problems. Skin disorders and allergies.

### Toxicological information on ingredients.

#### EPOXY RESIN (Number average MW <= 700 )

##### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 2,000.0

**Species** Rat

## STRONGCOAT WD RESIN CLEAR

### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub>) 2,000.0  
mg/kg)

Species Rat

### C13/15 ALKYLGLYCIDYL ETHER

### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub>) 5,000.0  
mg/kg)

Species Rat

## SECTION 12: Ecological Information

**Ecotoxicity** The product should not be allowed to enter drains, sewers or watercourses. The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

### 12.1. Toxicity

**Toxicity** Not available

**Acute toxicity - fish** Not determined

**Acute toxicity - aquatic invertebrates** Not determined.

**Acute toxicity - aquatic plants** Not determined.

**Acute toxicity - microorganisms** Not determined.

**Acute toxicity - terrestrial** Not determined.

**Chronic toxicity - fish early life stage** Not determined.

**Short term toxicity - embryo and sac fry stages** Not determined.

**Chronic toxicity - aquatic invertebrates** Not determined.

### Ecological information on ingredients.

#### EPOXY RESIN (Number average MW <= 700 )

**Acute toxicity - fish** LC50, 96 hours, 96 hours: 1.3 mg/l, Onchorhynchus mykiss (Rainbow trout)

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours, 48 hours: 2.1 mg/l, Daphnia magna

**Acute toxicity - aquatic plants** , 72 hours, 72 hours: > 11 mg/l, Freshwater algae

**Acute toxicity - microorganisms** EC<sub>50</sub>, 3 hours, 3 hours: > 100 mg/l, Activated sludge

### 12.2. Persistence and degradability

**Persistence and degradability** There are no data on the degradability of this product.



## STRONGCOAT WD RESIN CLEAR

<b>Phototransformation</b>	Not determined.
<b>Stability (hydrolysis)</b>	Not determined.
<b>Biodegradation</b>	Highly insoluble in water.
<b>Biological oxygen demand</b>	Not determined.
<b>Chemical oxygen demand</b>	Not determined.

### 12.3. Bioaccumulative potential

<b>Bioaccumulative potential</b>	No data available on bioaccumulation.
<b>Partition coefficient</b>	Not determined.

### 12.4. Mobility in soil

<b>Mobility</b>	The product is insoluble in water.
<b>Adsorption/desorption coefficient</b>	Not determined.
<b>Henry's law constant</b>	Not determined.
<b>Surface tension</b>	Not determined.

### 12.5. Results of PBT and vPvB assessment

<b>Results of PBT and vPvB assessment</b>	This substance is not classified as PBT or vPvB according to current EU criteria.
---	---

### 12.6. Other adverse effects

<b>Other adverse effects</b>	None known.
------------------------------	-------------

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Disposal methods</b>	Small quantities of product may be treated with an equivalent quantity of product hardener, allowed to cure and disposed of as low hazard waste. Large quantities should be disposed of via licensed waste operators to an approved incineration unit. Product containers must not be re-used without commercial cleaning.
-------------------------	--

## SECTION 14: Transport information

### 14.1. UN number

<b>UN No. (ADR/RID)</b>	3082
<b>UN No. (IMDG)</b>	3082
<b>UN No. (ICAO)</b>	3082

### 14.2. UN proper shipping name

<b>Proper shipping name (ADR/RID)</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (C13/15 ALKYLGLYCIDYL ETHER)
<b>Proper shipping name (IMDG)</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (C13/15 ALKYLGLYCIDYL ETHER)
<b>Proper shipping name (ICAO)</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (C13/15 ALKYLGLYCIDYL ETHER)
<b>Proper shipping name (ADN)</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (C13/15 ALKYLGLYCIDYL ETHER)

## STRONGCOAT WD RESIN CLEAR

### 14.3. Transport hazard class(es)

ADR/RID class	9
ADR/RID label	9
IMDG class	9
ICAO class/division	9

#### Transport labels



### 14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ICAO packing group	III

### 14.5. Environmental hazards

#### Environmentally hazardous substance/marine pollutant



### 14.6. Special precautions for user

EmS	F-A, S-F
Emergency Action Code	•3Z
Hazard Identification Number (ADR/RID)	90
Tunnel restriction code	(E)

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

#### SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>National regulations</b>	Control of Substances Hazardous to Health Regulations 2002 (as amended).
<b>Guidance</b>	Workplace Exposure Limits EH40. Safety Data Sheets for Substances and Preparations.
<b>Authorisations (Title VII Regulation 1907/2006)</b>	No specific authorisations are known for this product.
<b>Restrictions (Title VIII Regulation 1907/2006)</b>	No specific restrictions on use are known for this product.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

#### SECTION 16: Other information

<b>General information</b>	Don Construction Products Ltd. Technical Datasheet.
----------------------------	---

## STRONGCOAT WD RESIN CLEAR

<b>Key literature references and sources for data</b>	Health and Safety Executive Guidance Note EH40 (amended annually). Workplace Exposure Limits.
<b>Revision comments</b>	Section 9: update. Section 11 update. Section 12 update.
<b>Revision date</b>	08/06/2016
<b>Revision</b>	6
<b>Supersedes date</b>	25/04/2014
<b>SDS status</b>	Approved.
<b>Risk phrases in full</b>	R36/38 Irritating to eyes and skin. R43 May cause sensitisation by skin contact. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
<b>Hazard statements in full</b>	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.