



# Material SAFETY DATA SHEET

## Trowelite WP

### 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: **Trowelite WP**  
Description: Integral liquid waterproofing admixture for mortars  
Manufacturer: **Ayla Construction Chemicals**  
P.O. Box 1117, Amman 11118 Jordan  
Tel. + 962 6 5338891 Fax: + 962 6 5338829  
[www.dcp-int.com](http://www.dcp-int.com)  
Date Prepared: 09.06.16  
MSDS Number: DCP/01/01/02

### 2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition:	Water, silicic acid, potassium salt.			
Hazardous Ingredient(s)	Symbol	Risk Phrases	CAS No.	%
Water	-	-	7732-18-5	60 - 80
Silicic acid, sodium salt	C, Xi	R34, 36/37/38, 41	1312-76-1	15 - 30

Refer to Section 8 for Occupational Exposure Limits.

### 3: HAZARDS IDENTIFICATION

Hazard Information: Causes burns.  
Irritating to eyes, respiratory system and skin.  
Risk of serious damage to the eyes.

Classification: C, Xi. R34, 36/37/38, 41

### 4: FIRST AID MEASURES

Eyes: Immediately flush eyes with plenty of water for at least 15minutes. Lifting upper and lower eye lids occasionally. Get medical attention immediately.

Skin: Immediately flush eyes with plenty of water for at least 15minutes. Remove contaminated clothes and shoes. Get medical attention. Wash clothes before reuse.

Inhalation: Remove to fresh air. If not breathing give artificial respiration. If breathing is difficult give oxygen. Get medical attention.

Ingestion: Do not induce vomiting. Give large quantities of water. Never give anything by mouth to unconscious person. Get medical attention immediately.



## 5: FIRE FIGHTING MEASURES

Extinguishing Media: Carbon dioxide, powder, foam or water. Don't Use water jets.  
Personal Protective Equipment: Self-contained breathing apparatus and full protective clothing.

## 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Caution! Floor and other surfaces may be slippery. Ventilate area of leak or spill. Wear suitable protective clothing, gloves and eye/face protection.  
Environmental Precautions: Prevent entry into drains, sewers and water courses.  
Decontamination Procedures: Recover liquid when possible, collect liquid in appropriate container or soak up with inert absorbent such as sand. Gather into labeled containers. Dispose off as applicable regulations.

## 7: HANDLING AND STORAGE

Handling: Maintain good standards of personal hygiene. Avoid skin and eye contact. Do not eat, drink or smoke whilst using this product. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.  
Storage: Keep container tightly closed in a cool dry area away from sources of heat and out of direct sunlight to avoid pressure build up. Store in conformity with local fire regulations. Store away from sources of ignition.

## 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Eye Protection: Use chemical safety goggles and/or a full face shield where splashing is possible.  
Skin Protection: Wear impervious clothing, including boots, gloves, lab coats, aprons or coveralls.  
Respiratory Protection: A system of local and/or general exhaust is recommended to keep employee below the Airbone Exposure Limit. If the exposure limit is exceeded, a half-face dust/mist respirator may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respiratory supplier.  
Hygiene Measures: Change contaminated clothing and clean before re-use.  
Engineering Controls: Use only in well ventilated areas. Local exhaust ventilation is recommended.  
Exposure Guidelines: OSHA PEL  
Sodium silicate 80 mg/m<sup>3</sup>



## 9: PHYSICAL AND CHEMICAL PROPERTIES

Form:	Liquid
Colour:	Pink
Odour:	Odourless
Relative Density (@25°C):	1.03 - 1.05
Water Solubility:	Soluble

## 10: STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Chemical Incompatibility:	Fluorine, mineral acids, organic acids, organic materials.
Hazardous Polymerization:	Will not occur.

## 11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components.  
Acute Oral effect LD50 > 2000 mg/kg (rat).

### Health Effects

On Eyes:	A strong alkaline irritant. Alkaline exposures produce severe irritation with effects similar to dose of dilute caustics. Inflammation or burns with possible damager to the eye tissues can occur together with tearing and considerable pain.
On Skin:	A strong alkaline irritant. Causes severe irritation. Symptoms include redness, itching and pain. Dries to form a glass film which can cut skin. Solid sodium silicate: dermal contact with alkaline corrosives ma produce pain, redness, severe irritation or full thickness burns.
By Inhalation:	A strong alkaline irritant. Inhalation can cause severe irritation of mucous membranes and upper respiratory tract. Sumptoms may include burning sensation, coughing, wheezing, laryngitis, shortness of breath, headache, nausea and vomiting. High concentrations may cause long damage.
By Ingestion:	A strong alkaline irritant. Causes irritation to the gastrointestinal tract. Symptoms may include nausea, vomiting and diarrhea. Solid sodium silicate: Alkaline corrosive ingestion may produce burns to the lips, tongue, oral mucosa, upper airway, esophagus and occasionally stomach.

## 12: ECOLOGICAL INFORMATION

Environmental Assessment:	Not determined.
Mobility:	Viscous liquid.
Degradability:	Not determined.
Bioaccumulation:	Not determined.
Environmental Toxicity:	96hr LC50 Lepomis macrochirus: 301 – 478 mg/ltr. 96hr LC50 Brachydanio rerio: 3185 mg/ltr. 96hr LC50 Daphnia magna: 216 mg/ltr.

## 13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product:	Dispose off through an authorized waste contractor to a licensed site.
Used/ Contaminated Product:	As for unused product.
Packaging:	Must be disposed off through an authorized waste contractor.

## 14: TRANSPORT INFORMATION

This product is **not** classified as dangerous for transport.

## 15: REGULATORY INFORMATION

### Hazard Label Data:

**Xi**



**Harmful**

**C**



**Corrosive**

### Risk Phrases:

R34	Causes burns
R36/37/38	Irritating to eyes, respiratory system and skin.
R41	Risk of serious damage to the eyes.

### Safety Phrases:

S24/25	Avoid contact with skin and eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37/39	Wear suitable protective clothing, gloves and eye/face protection.



## 16: OTHER INFORMATION

Issue Date: 09/06/2016 Revised Date: 29.11.2017

Disclaimer: The information contained herein is derived from the best available sources and is believed to be accurate. However, no guarantee is expressed or implied regarding the accuracy of the data given in the use of this product.