

Material SAFETY DATA SHEET Trowelite WP

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name:	Trowelite WP
Description:	Integral liquid waterproofing admixture for mortars
Manufacturer:	Ayla for Building Materials Industry & Trade
	Al-Karadeh, Arsat Al-Hindia, Baghdad
	Tel.: +964 790 1488 730
	www.dcp-int.com
Date Prepared:	09.06.16
MSDS Number:	DCP/01/01/02

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition:	Water, silicic acid, potassium salt.			
Hazardous Ingredient(s)	Symbol	Risk Phrases	CAS No.	%
Water	-	-	7732-18-5	60 - 80
Silicic acid, sodium salt	C, Xi	R34, 36/37/38, 41	1312-76-1	15 – 30

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

Hazard Information:	Causes burns. Irritating to eyes, respiratory system and skin. Risk of serious damage to the eyes.	
Classification:	C, Xi. R34, 36/37/38, 41	
4: FIRST AID MEASURES		
Eyes:	Immediately flush eyes with plenty of water for at le upper and lower eye lids occasionally. Get medical at	•
Skin:	Immediately flush eyes with plenty of water for Remove contaminated clothes and shoes. Get me clothes before reuse.	
Inhalation:	Remove to fresh air. If not breathing give ar breathing is difficult give oxygen. Get medical attent	•
Ingestion:	Do not induce vomiting. Give large quantities of anything by mouth to unconscious person. Go immediately.	
Issue No.: 01 Rev. No.:	01 Trowelite WP	Page 1 of 5



5: FIRE FIGHTING MEASURES

Extinguishing Media:	Carbon dioxide, powder, foam or water. Don't Use water jets.
Personal Protective Equipment:	Self-contained breathing apparatus and full protective clothing.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Caution! Floor and other surfaces may be slippery. Ventilate area of leak or spill. Wear suitable protective clothing, gloves and eye/face protection.
Environmental Precautions:	Prevent entry into drains, sewers and water courses.
Decontamination Procedures:	Recover liquid when possible, collect liquid in appropriate container or soak up with inert absorbent such as sand. Gather into labeled containers. Dispose off as applicable regulations.

7: HANDLING AND STORAGE

Handling:	Maintain good standards of personal hygiene. Avoid skin and eye contact. Do not eat, drink or smoke whilst using this product. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.
Storage:	Keep container tightly closed in a cool dry area away from sources of heat and out of direct sunlight to avoid pressure build up. Store in conformity with local fire regulations. Store away from sources of ignition.

8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Eye Protection:	Use chemical safety go possible.	oggles and/or a full face shield where splashing is
Skin Protection:	Wear impervious cloth coveralls.	ing, including boots, gloves, lab coats, aprons or
Respiratory Protection:	employee below the exceeded, a half-face times the exposure lim	nd/or general exhaust is recommended to keep Airbone Exposure Limit. If the exposure limit is dust/mist respirator may be worn for up to ten hit or the maximum use concentration specified by cory agency or respiratory supplier.
Hygiene Measures:	Change contaminated	clothing and clean before re-use.
Engineering Controls:	Use only in well recommended.	ventilated areas. Local exhaust ventilation is
Exposure Guidelines:	OSHA Sodium silicate	PEL 80 mg/m ³

Issue No.:	01	Rev. No.:	01	
------------	----	-----------	----	--



9: PHYSICAL AND CHEMICAL PROPERTIES

Form:	Liquid
Colour:	Pink
Odour:	Odourless
Relative Density (@25°C):	1.03 - 1.05
Water Solubility:	Soluble

10: STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Chemical Incompatibility:	Fluorine, mineral acids, organic acids, organic materials.
Hazardous Polymerization:	Will not occur.

11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Acute Oral effect LD50 > 2000 mg/kg (rat).

Health Effects

On Eyes:	A strong alkaline irritant. Alkaline exposures produce severe irritation with effects similar to dose of dilute caustics. Inflammation or burns with possible damager to the eye tissues can occur together with tearing and considerable pain.
On Skin:	A strong alkaline irritant. Causes severe irritation. Symptons include redness, itching and pain. Dries to form a glass film which can cut skin. Solid sodium silicate: dermal contact with alkaline corrosives ma produce pain, redness, severe irritation or full thickness burns.
By Inhalation:	A strong alkaline irritant. Inhalation can cause severe irritation of mucous membranes and upper respiratory tract. Sumptons may include burning sensation, coughing, wheezing, laryngitis, shortness of breath, headache, nausea and vomiting. High concentrations may cause long damage.
By Ingestion:	A strong alkaline irritant. Causes irritation to the gastrointestinal tract. Symptons may include nausea, vomiting and diarrhea. Solid sodium silicate: Alkaline corrosive ingestion may produce burns to the lips, tongue, oral mucosa, upper airway, esophagus and occasionally stomach.



12: ECOLOGICAL INFORMATION

Environmental Assessment:	Not determined.
Mobility:	Viscous liquid.
Degradability:	Not determined.
Bioaccumulation:	Not determined.
Environmental Toxicity:	96hr LC50 Lepomis macrochirus: 301 – 478 mg/ltr. 96hr LC50 Brachydanio rerio: 3185 mg/ltr. 96hr LC50 Daphnia magna: 216 mg/ltr.

13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product:	Dispose off through an authorized waste contractor to a licensed site.	
Used/ Contaminated Product:	As for unused product.	
Packaging:	Must be disposed off through an authorized waste contractor.	

14: TRANSPORT INFORMATION

This product is **not** classified as dangerous for transport.

15: REGULATORY INFORMATION

Hazard Label Data:	Xi	C Corrosive
Risk Phrases:		
	R34	Causes burns
	R36/37/38	Irritating to eyes, respiratory system and skin.
	R41	Risk of serious damage to the eyes.
Safety Phrases:		
	S24/25	Avoid contact with skin and eyes.
	S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
	S36/37/39	Wear suitable protective clothing, gloves and eye/face protection.

Issue No.:	01	Rev. No.:	01	Trowelite WP	Page	4 of 5



16: OTHER INFORMATION

Issue Date:

09/06/2016

Revised Date: 29.11.2017

Disclaimer: The information contained herein is derived from the best available sources and is believed to be accurate. However, no guarantee is expressed or implied regarding the accuracy of the data given in the use of this product.

Issue No.:	01	Rev. No.:	01	
------------	----	-----------	----	--